Callies Part #		Duration@0.050"		Advertised Duration		Cam Lift		Valve Lift			Lobe CL		Lift@TDC		Remarks
Godzilla	Solid / HYD	Intake	Exhaust	Intake	Exhaust	Intake	Exhaust	Intake	Exhaust	LSA + Advance	Intake	Exhaust	Intake	Exhaust	
175-001	HR	220	226	276	282	0.350	0.345	0.630	0.621	115+6	109	121	0.053	0.032	WORKS w/ Stock Pistons - Nice boosted cam for stock engine.
175-002	HR	220	226	276	282	0.350	0.345	0.630	0.621	111+6	105	117	0.064	0.040	WORKS w/ Stock Pistons - We call this one "Truckzilla". Great NA cam for stock engine. 600 hp - 600 tq RPM range: 2500-6200
175-008	HR	220	226	276	282	0.350	0.345	0.630	0.621	109+5	104	114	0.068	0.047	WORKS w/ Stock Pistons - Same as 175-002, except tighter LSA. Slightly more power, but reduced range. 2800-6200
175-006	HR	224	230	288	295	0.375	0.376	0.675	0.677	115+6	109	121	0.059	0.037	WORKS w/ Stock Pistons - Similar to 175-001, except more lift and duration.
175-009	HR	230	242	281	291	0.368	0.368	0.662	0.662	111+5	106	116	0.079	0.066	Nice NA cam for increased rpm and power in modified engine. 650+ hp. RPM range: 3200-6500
175-011	HR	230	250	281	299	0.368	0.368	0.662	0.662	111+5	106	116	0.079	0.066	175-009 w/ 250 exhaust duration. Gained 15hp above 5000 rpm - lost a little torque down low
175-005	HR	232	244	287	296	0.350	0.345	0.630	0.621	115+5	110	120	0.068	0.056	Works well with Procharger. 1100+ HP w/F1A
175-013	HR	234	246	285	295	0.368	0.368	0.662	0.662	112+5	107	117	0.083	0.069	NA cam for modified engine with aftermarket intake. Great power in 3800- 6800 RPM range.
175-012	HR	238	246	294	313	0.353	0.353	0.635	0.635	116+5	111	121	0.074	0.057	Good turbo cam for modified engine at higher RPM.
175-007	HR	240	250	314	324	0.375	0.375	0.675	0.675	111+6	105	117	0.095	0.072	Street / track cam for modified engine. 675+ hp. RPM range: 4000-6800
175-014	HR	244	256	294	308	0.368	0.366	0.662	0.659	114+5	109	119	0.091	0.078	Street / track cam for modified engine with aftermarket intake. 700ish HP. RPM range: 4200-7200
175-004	HR	254	264	328	338	0.362	0.362	0.652	0.652	112+5	107	117	0.109	0.092	High rpm cam for modified engine with aftermarket intake. 690 hp - 550 tq RPM range: 4500-7500
175-003	HR	254	264	328	338	0.362	0.362	0.652	0.652	116+6	110	122	0.099	0.077	Same as 175-004, except wider LSA. 676 hp - 540 tq.
175-010	HR	254	264	328	338	0.362	0.362	0.652	0.652	118+6	112	124	0.093	0.071	Same as 175-003, except wider LSA. Intended for large centrifugal blower in the 1500+ HP range.